

Tractors

XERION 5000 4500 4200



## Working hard to make your job easier.



Pile on the work.







Innovations







Discover the XERION. xerion.claas.com

## Power equals efficiency.



## Three versions. Unique build concept.

There is nothing quite like the XERION. You'd recognise it instantly: four equal-sized wheels on two steered axles, full-frame construction for carrying enormous loads, continuously variable transmission up to 530 hp and the intuitive operation that you only get from CLAAS.

- TRAC with fixed cab (page 8)
- TRAC VC with rotating cab (page 10)
- SADDLE TRAC with room for a mounted tank (page 12)

## Six benefits. Endless possibilities.

- Four equal-sized wheels or dual tyres convert engine power into tractive power
- Two steered axles offer five steering modes for a wide range of applications
- Add up to 6.8 t ballast at the front and rear
- The fully load-bearing frame can support loads of up to 15 t per axle
- Continually variable transmission delivering up to 530 hp helps you to reduce fuel consumption
- Operate the XERION intuitively with the CEBIS touchscreen

# XERION TRAC. Unbeatable in the field.

## TRAC with central cab.

The XERION TRAC is the best option if arable work is your main focus. It has a suspended comfort cab in the middle of the vehicle and large windows for unique all-round visibility.

## The benefits for you.

- In the field you have the advantage of high traction and enormous pulling power
- Ballasting and a swan neck hitch ensure that all loads are evenly distributed cross the two driven axles
- The large tyre contact area protects the soil

## Applications.

## Tillage.

Four equal-sized wheels provide excellent tractive power. The weights are ideally distributed and the machine is very easy to ballast.

## Drilling.

You can achieve high work rates and save fuel thanks to the carefully tuned engine management system.

## Field transport.

Superb pulling power gets the job done quickly. The CMATIC transmission offers a high level of driving comfort.

## Slurry application.

Power hydraulics deliver 250 l/min. The turning circle is just 15.7 m and crab steering protects the soil.



## XERION TRAC VC.

## Reversing has never been so comfortable.

## TRAC VC with the rotating cab.

Some applications require particularly good visibility to the rear of the tractor. The rotating cab (VC stands for Variable Cab) is the most convenient reverse-drive system imaginable. At the press of a button, you can rotate the entire cab from its central position to the rear-facing position above the rear axle in seconds.

## The benefits for you.

- Perfect view of rear attachments
- The controls rotate automatically with the cab
- All functions remain the same when operating in the rear position
- The armrest with integrated CEBIS touchscreen makes it even more straightforward to operate
- Enjoy a high level of on-road comfort with the cab in the central position

## Applications.

## Silo operations.

Enormous pushing power combined with crab steering for optimal compaction.

## Wood chipping.

The XERION is ready to go, with excellent all-round visibility and plenty of power through the PTO.

### Mulching

High power is delivered to the PTO even at low speeds, reducing your hourly fuel consumption.

## Snow blowing.

CMATIC enables precision driving from a speed of 0.05 km/h. Ground clearance is impressive and you get an unrestricted view.



# XERION SADDLE TRAC. It won't let you down.

## Plenty of room for mounted implements.

In the SADDLE TRAC, the cab is in a fixed position above the front axle, leaving ample space behind the cab for a wide variety of implements. A mounted tank, for example, turns the XERION into a self-propelled manure spreader with plenty of power left for slurry application and incorporation.

The XERION SADDLE TRAC is a dependable load carrier you can also rely on to do any other jobs on your farm that call for a large tractor.

## The benefits for you.

- A range of mounted implements turn the SADDLE TRAC into a fully self-propelled vehicle
- Even load distribution allows you to get out onto your fields much earlier in the spring
- Four large tyres combined with crab steering help to protect the soil even during heavy draught work
- With 462 hp and 2,200 Nm torque, the XERION 4200 has ample reserves

## Applications.

## Manure and digestate spreading.

Power hydraulics deliver 250 l/min. The turning circle is just 15.7 m.

## Drilling and fertiliser application.

Get onto the field earlier in the spring and have enough capacity for high work rates.

## Silo operations.

The impressive pushing power of the front linkage ensures optimal compaction on the silage clamp.





## Power where you need it.

## Impressive performance.

CLAAS POWER SYSTEMS combines powerful 6-cylinder Mercedes-Benz engines with a simple drive train. Enormous torque is available with all three machines even in lower engine speed ranges. The XERION 5000 delivers a maximum torque of 2,600 Nm when the PTO is switched on. The low-speed concept reduces the engine idling speed from 800 rpm to 730 rpm.

## 462 hp even in the XERION 4200.

We have increased the engine output of the XERION 4200 by 27 hp, so drivers can now enjoy more torque at lower engine speeds – as well as enhanced driving dynamics, large power reserves and reduced fuel consumption.

- 2,200 Nm maximum torque
- Smoother running
- More power and agility





## Integrated exhaust gas aftertreatment.

- Stage V thanks to SCR technology, diesel particulate filter (DPF) and diesel oxidation catalyst (DOC)
- Tucked away under the cab

## Designed to save fuel.

- Engine output of XERION 4200 increased by 27 hp
   to 462 hp
- Extremely powerful engines even in the low speed range
- Constant torque curve at high level
- Exhaust gas aftertreatment fully integrated without impeding visibility
- Intelligent cooling with fuel-saving fan speed control
- Radiators can be cleaned on the move by pressing a button to reverse the fan wheel

XERION		5000	4500	4200
Number of cylinders		6	6	6
Cubic capacity	cm <sup>3</sup>	12800	12800	10700
Output at nominal engine speed (ECE R 120) <sup>1</sup>	kW/hp	374/509	353/480	337/458
Max. output (ECE R 120)1	kW/hp	390/530	360/490	340/462
Max. torque (ECE R 120)1	Nm	2600	2400	2200

<sup>&</sup>lt;sup>1</sup> Meets ISO TR 14396

## Latest generation engines.

- 6-cylinder in-line Mercedes-Benz engines
- Maximum output from 462 to 530 hp
- Common rail injection and 24 V starter motor



# Continuously variable transmission for enhanced driving comfort.

## Unique in this hp class.

The CMATIC continuously variable transmission from ZF is in a class of its own. From 0.05 to 50 km/h you have the benefit of outstanding driving comfort as well as efficient power transmission provided by a high mechanical component.

The linear drivetrain ensures that engine power reaches the axles and PTO by the most direct route. Selectable longitudinal and transverse differentials provide optimum power transfer.

The accelerator pedal and multifunction control lever are designed for simple and intuitive operation. During field work or at constant PTO speed the ground speed automatically adapts to the conditions. You can reduce fuel consumption noticeably by making simple adjustments to the engine droop settings.




## Short transfer times at 40 or 50 km/h.

The wheeled versions of the XERION can reach speeds of up to 30 km/h depending on the type of transmission. With the cab rotated, you can also travel backwards at up to 30 km/h.

## Standing firm.


The XERION slows to a stop as soon as the driver takes their foot off the accelerator. There is no need to apply the brakes – the tractor remains stationary.



## Power equals efficiency.

- CMATIC transmission technology for continuously variable driving comfort from 0.05 to 50 km/h
- Linear drivetrain configuration for direct transfer of engine power
- Permanent four-wheel drive
- Four automatically activated driving ranges for high efficiency
- Large contact area for enormous tractive performance
- User-friendly operation via accelerator pedal or multifunction control lever

## Five steering modes make it remarkably agile.



## Built for extreme loads.


The XERION is ideal for carrying heavy loads thanks to its unique frame construction. Bolted rather than welded crossbeams in the frame provide greater strength and load-carrying capacity. The heavy-duty axles are designed to carry loads of up to 15 t per axle at speeds of up to 50 km/h. Despite its size and weight, with two steered axles the XERION is remarkably agile and manoeuvrable.

The 110 mm ball hitch for attaching large slurry tankers is located immediately behind the cab. It distributes the load of the attached tanker across both axles, while the long 3.6 m wheelbase provides a high level of driving comfort.


## Stability you can count on every day.


- Durable, extremely robust full frame
- Heavy-duty axles with 15 t axle load up to 50 km/h
- Fully integrated linkage with load capacities of up to 8.4 t at the front and 13.6 t at the rear














## The right steering for even job.

The two steering axles on the XERION can be steered in five different ways, and remain active at the headland.

## 1 Standard steering program.

- Four-wheel and front-axle steering combined
- From 5° steering lock on the front axle, the rear axle follows the front axle electrohydraulically
- The steering lock is continuously reduced from 12 km/h
- Fully locked at 40 km/h

## DYNAMIC STEERING option.

- The number of turns of the steering wheel needed to reach maximum wheel lock is significantly reduced according to the speed.
- More comfortable and dynamic turning at the headland

## 2 Four-wheel steering.

- Rear axle is steered at the same time as the front axle but in the opposite direction
- Axles move simultaneously

## 3 Single-sided crab steering.

Rear axle controlled separately via the CMOTION multifunction control lever

## 4 Gentle mode (reduced crab steering).

- Rear axle moves along a parallel track to front axle
- 75% of steering lock can be used
- Steering corrected up to 4° by the steering wheel via the front axle

## 5 Full crab steering.

- Rear axle moves along a parallel track to front axle
- Rear axle steered once via the CMOTION multi-function control lever
- Minor steering corrections possible

## Power to the ground.



## Two power transmission options.

With the XERION you have two options for transferring its power to the ground via both axles: four equal-sized wheels, or dual tyres that double the contact area.



## Four equal-sized wheels.

- Excellent soil protection and good ground-contour tracking
- With a diameter of 2.16 m
- Footprint approx. 3.7 m<sup>2</sup> with 900/60 R 42 tyres and 1 bar internal tyre pressure
- No more than 3 m wide with 710/75 R 42 and 750/70 R 44 tyres
- Comfortable road travel at up to 40 or 50 km/h
- Optional tyre pressure control system controlled via the CEBIS on-board information system
- Maximum traction and less slip
- Plenty of tractive power





- Dual tyres for a high level of soil protection
- Suitable for tyre dimensions 650/85 R 38, 710/70 R 42 and 710/75 R 42
- Rims on outer wheels are firmly bolted to the inner rims with spacer rings
- Split spacer rings allow for rapid removal of the outer wheels for road travel (< 3 m)</li>



## Get the ballasting right for optimum efficiency.

## Fuel-efficient ballasting.

Tractors all too often carry too much weight. But over-ballasting does not boost tractive performance – it simply increases fuel consumption. With the XERION it's easy to adjust the ballasting precisely to suit the task. The 400 kg ballast plates can be quickly fitted or removed and firmly secured with quick-release fasteners.

## Front ballast.

You can add 3,400 kg of ballast to the front of the XERION. The base weight weighs 1,800 kg and can take up to four additional 400 kg plates. It is available in two versions: one that can be attached to the front linkage and one that is fixed permanently in place.

## Rear ballast.

The rear of the XERION can also be ballasted with 3,400 kg. A 1,000 kg fixed (but removable) base plate can accommodate six additional plates each weighing 400 kg. These can be quickly added or removed with a telehandler, wheel or front

## Three ballasting tips.

- 1 As much as necessary, as little as possible
- 2 In the field, the need for ballasting decreases as the ground speed increases
- 3 During field work, tyre slip should average more than 6%, otherwise the tractor is carrying too much ballast





Variable front-mounted ballasting.

Rear ballasting up to 3,400 kg.



Max. ground speed under full load	Max. permitted vehicle weight (incl. drawbar load of attachment in t.)
8 km/h	24 t
10 km/h	22.5 t
12 km/h	18.5 t

It's a good idea to estimate in advance the speed at which you plan to work with the attached implement. For example, if you ballast for a speed of 8 km/h  $\,$ and then work at 12 km/h, you're carrying almost 6 t of excess ballast. This has a noticeable effect on fuel consumption.

## The right weight for every application.

- Add up to 3,400 kg of ballast at the front and the rear
- Weights are easy to add and remove
- All plates are held securely in place with a quick-release mechanism
- Get the ballast right and save fuel

## Creating a strong attachment.




## Hitch points and PTO for heavy loads.

With the XERION you can choose from a range of hitching options. Whether swan neck attachment, drawbar or trailer coupling, all systems are designed for high load-carrying capacity.

When the PTO is running at 1,000 rpm, the XERION develops its output at a reduced engine speed of 1,730 rpm. Thanks to the simple drive train design, much of the rated output is transferred to the PTO stub. This enables you to reduce your fuel consumption even when the XERION makes the full PTO output available.

## Rest assured.

- All hitching systems are designed for high load-carrying capacity
- The swan neck hitch can take a drawbar load of up to 15 t
- The PTO provides full power even at reduced engine speed
- The PTO stubs can be replaced quickly and easily
- You have a choice of different drawbars with:
- a 40 or 50 mm diameter locking pin
- an 80 mm hitch ball
- a Piton-Fix coupling



### Swan neck.

The swan neck coupling with its 110 mm hitch ball is designed to take a drawbar load of up to 15 t, which it distributes evenly across both axles. This type of hitch gives a smaller turning radius and a much shorter combination length than a tractor with a rear-mounted slurry tanker, for example.



### Different drawbar hitches.

With drawbar hitches you have a choice of an 80 mm hitch ball or 38 and 50 mm diameter pin. With three holes, you can vary the position of the attachment point. So whatever the application, you can always maintain the right distance from the rear axle.



## High drawbar loads.

The XERION can take on any challenge. With the range of hitch options, it can take a drawbar load of up to 5 t.

- D50 pins (Ø 50 mm)
- D70 pins (Ø 70 mm)



## Quick-change PTO stubs.

The PTO stubs can be replaced quickly and securely. Choose from the following sizes:

- 1¾", 6 splines
- 1¾", 20 splines
- 21/4", 22 splines (Ø 57.7 mm)

## Untap its full potential.









## Hydraulic output of up to 442 l/min

The XERION provides ample hydraulic power for special applications such as digestate spreading. The hydraulic circuits can be controlled via the CMOTION multifunction control lever. You can assign all ten function buttons to individual hydraulic functions.

The XERION has a pump transfer gearbox to satisfy even higher hydraulic requirements. A hydraulic pump with an output of 197 l/min is mounted to the pump transfer as standard. A second hydraulic pump (load sensing) supplies a further 225 l/min for the four, five or six spool valves. And of course the proven additional power hydraulic system with a separate circuit delivering with 250 l/min is optionally available for attachments such as liquid manure tanks.

## Power Beyond at front and rear.

Power Beyond connections with large-diameter lines, flat-seal hydraulic couplings and hydraulic return line provide a high oil delivery rate with low losses.

The XERION has three double-acting spool valves at the front (max. two spool valves if a front linkage is installed). Seven further double-acting spool valves are available at the rear. With quick-release couplings, you can connect and disconnect them rapidly without risk of oil leaks.



## Enough pressure.

- Three hydraulic circuits supply your attached or mounted implements reliably and powerfully
- Up to ten double-acting spool valves available at the front and rear
- The pump transfer gearbox mounted on the engine enables hydraulic outputs of up to 442 l/min
- Strong power hydraulics perform convincingly even at low engine speeds
- Power Beyond connections with large-diameter lines maximise flow
- Conveniently controlled via the CMOTION multifunction control lever

## Power means versatility.



## Power enough for any job.

With an enormous continuous lift capacity of 8.1 t at the front and 10 t at the rear, the XERION handles even very heavy implements effortlessly.

With the CMOTION multifunction control lever you can control the front and rear linkage easily with your thumb without having to move your hand. This high level of operating comfort means that on long working days you can work quickly and accurately without tiring.

## Equipped for any challenge.

- Continuous 8.1 t lift capacity at the front and 10 t at the rear
- Vibration damping for safe and comfortable working
- Reinforced front linkage for silage clamp work
- Pivoting rear linkage for the SADDLE TRAC (optional)
- Convenient control via the CMOTION multifunction control lever



## 8.1 t lift capacity at the front.

The sturdy front linkage (1) is fully integrated into the frame. The lower links fold in easily to reduce the vehicle length.

- Double-acting ram with continuous 8.1 t lift capacity
- Quick and easy to attach front weights



When using the TRAC, TRAC VC or SADDLE TRAC in the silage clamp, you can fit a reinforced front linkage (2) which can accommodate a dozer blade up to 4.0 m wide. Shear bolts protect the linkage from damage.



## 13.6 t lift capacity at the rear.

The rear linkage (3) is equipped with vibration damping and category IV N hooks. For the top attachment point on the 3-point hitch at the rear, you can choose from a mechanical or hydraulic top link.

- Double-acting rams with max. 13.6 t (10 t continuous) lift capacity
- Hydraulic side stabilisers with a high level of operator comfort
- Mechanical side stabilisers or internal reinforcement
- Robust ball ends for extended periods working with the same implement (optional)

A pivoting rear linkage (4) is available for the SADDLE TRAC. This allows you to use a low-compaction offset mode, for example when spreading slurry on sensitive grassland areas.



## Comfort and concentration go hand-in-hand.





The TRAC VC has the most convenient reverse-drive system on the market. Its cab can be rotated through  $180^\circ$  in less than 30 seconds.



With 22 work lights, the XERION turns night into day. A premium LED lighting package is available on request.

## Comfortable, clearly laid out and quiet.

We have designed the XERION cab so there is nothing to distract you. Virtually no vibrations, exceptional all-round visibility, pleasantly low noise levels. With the CMOTION multifunction control lever and the armrest with integrated CEBIS touch-screen, you can control the tractor intuitively with just three fingers. The new CEMIS 1200 terminal is also within easy reach.

## The XERION comfort cab.

- Generously sized cab
- Large, heated windows for a perfect all-round view
- Outstanding sound proofing (only 69 dB max.)
- Intelligent semi-active cab suspension
- Rotating cab provides the most convenient reverse-drive system on the market (TRAC VC)
- Intuitive CMOTION multifunction control lever

- 12" CEBIS monitor with touchscreen
- CEMIS 1200 terminal with intuitive user interface
- 3-way adjustable steering column
- Air conditioning and auxiliary heating
- 360 degree windscreen wiper on the front windscreen
- Sun blinds on all four sides (optional)
- Lights activated from the steps

## It's got everything you need to make your job easier.

- Comfortable swivel seat with optional leather cover
- Heated windows for good visibility whatever the
- Armrest with integrated CEBIS touchscreen for efficient operation
- Intuitive CEMIS 1200 terminal for precise guidance and documentation

## The XERION – outstanding ergonomics.

## We've listened to our drivers.

We worked with our customers and drivers to develop the control concept specifically for large CLAAS tractors. The driver's arm and hand stays in a relaxed position without tiring. The clearly arranged control and function buttons are labelled with self-explanatory symbols.

### Three-finger operation.

The CMOTION multifunction control lever allows you to control complex processes with up to four control functions intuitively using only your thumb, index and middle finger – so you can work in comfort with your hand resting in a natural position.

## Everything under control with CEBIS.

The height-adjustable armrest incorporates the 12" CEBIS touchscreen which allows you to navigate the main and submenus with ease. All operating states are clearly displayed and you can adjust the machine settings in just a few steps.



## 1 CEBIS touchscreen.

You can choose between two screen layouts (road or field), each with self-explanatory symbols and colour coding. The DIRECT ACCESS function with the machine silhouette give you rapid access to the sub-menus. A high-resolution camera helps you to work with inch-perfect precision.

## 2 CEBIS rotary pushbutton.

Use it to navigate the CEBIS menu reliably even on bumpy ground. The DIRECT ACCESS button takes you straight to the last activated tractor functions.

## 3 Clearly laid-out control panel.


Use the self-explanatory controls to operate the basic functions. For example, you can switch the PTO or differential lock on or off, control the linkage or position the front and rear linkage.

## 4 CMOTION multifunction control lever.

The ergonomic CMOTION multifunction control lever makes light work of complex operations at the headland.

## All machine functions at a glance.


- Intuitive control concept for efficient work
- Rapid CEBIS navigation via touchscreen or rotary pushbutton
- CMOTION multifunction control lever for three-finger control of the machine
- Clearly laid out controls with self-explanatory symbols
- CEMIS 1200 terminal for efficient precision farming



### 5 Intuitive CEMIS 1200 terminal.

The CEMIS 1200 terminal fits seamlessly into the cab and shares the same intuitive control logic as CEBIS, so you'll soon find your way around. You can use the system on all CLAAS machines set up for GPS PILOT CEMIS 1200, and transfer the terminal and receiver from one machine to another in next to no time.

- Intuitive user interface for outstanding ease of use day and night
- Quick access to all important functions
- Freely configurable working areas for custom control
- Easy activation of new functions allows you to respond flexibly to changing requirements
- Transfer new licences online or activate directly on the terminal
- Automatic section switching with ISOBUS TC Section Control for precise, stress-free work
- Precision farming and documentation with ISOBUS TC-GEO and VRA
- Rapid transfer of all task data via mobile phone connection



## Perfect turning manoeuvres in next to no time.

## CLAAS SEQUENCE MANAGEMENT (CSM).

CSM headland management takes the load off you whenever you need to manoeuvre at the headland. You can run any previously recorded functions simply by pressing a button.

The following functions can be combined in any order:

- Spool valves with time and flow control
- Four-wheel drive, differential lock and front axle suspension
- Front and rear linkage
- Cruise control
- Front and rear PTO
- Engine speed memory



With CEBIS
Four per implement,
up to 20 implements
CMOTION and
F buttons
On CEBIS display
Time- or distance-
related
Subsequent sequence optimisation
in CEBIS



Activate the sequence using the F buttons on the CMOTION control lever

## Take it easy at the headland.

- CSM automates your turning manoeuvres
- You can record, vary, optimise and automatically run up to four sequences





## Easy to record and run.

Sequences can be recorded on a distance- or time-related basis. In recording mode, clear symbols guide the driver step-by-step through the process of creating the sequence on the CEBIS. A sequence that is running can be paused and restarted simply by pressing a button.

## Non-stop optimisation with CEBIS.

Recorded sequences can be changed and optimised in CEBIS at a later date. Steps can be added and deleted or changed and adapted in minute detail, allowing times, distances and flow volumes to be tailored to current conditions. Once a sequence has been recorded, it can be refined down to the last detail in just a few steps.

# GPS PILOT CEMIS 1200. Precision farming made easy.

Precise, future-proof, simple.

Improve the profitability of your farm and simplify day-to-day operations – step into the future with the GPS PILOT CEMIS 1200.

With the GPS PILOT automatic steering system, your machine will seem like it's running on rails: always on the right track, using the full working width with no overlapping.

The CEMIS 1200 fits seamlessly into the cab: with the same intuitive control logic as CEBIS, operators will quickly find their way around.

You can use the system on all CLAAS machines set up for GPS PILOT CEMIS 1200. The terminal and receiver can be transferred from one machine to another in next to no time, giving you complete flexibility and saving money.

Thanks to ISOBUS and standard data exchange formats, the CEMIS 1200 is the way forward for more precision in farming.

### Reference track planning.

Plan your reference tracks with ease – record reference tracks spontaneously or use reference track management on the CEMIS 1200 to plan your tracks based on field boundaries. Pre-planned reference tracks can also be transferred to the terminal. CEMIS 1200 provides various different drive modes which enable you to maximise the efficiency of your fieldwork.

In addition, tramline management prompts you to create a tramline in the right position. Tramlines are highlighted in colour on the screen, giving you a perfect overview of your work. You can also activate an acoustic signal.

### Benefits:

- Intuitive user interface for outstanding ease of use day and night
- Quick access to all important functions
- Freely configurable working areas for custom control
- The fast and easy way to start fieldwork



### Precision guidance.

You need a good correction signal for precise work. It's a given with SATCOR 15<sup>1</sup> as standard for 5 years.

## Need even greater accuracy?

Choose the optional SATCOR 3¹ and SATCOR 3 FAST¹ correction signals (± 3 cm).

## Absolute precision your top priority?

Choose the GPS PILOT CEMIS 1200 with RTK correction signal for the highest possible repeatable accuracy (± 2-3 cm).

### RTK Bridging.

All RTK correction signals are enhanced by the RTK Bridging function as standard, so if the signal is lost, work can continue for up to 20 minutes with gradually decreasing accuracy.

## Difficult topography or mobile phone dead zones in your area?

With RTK Bridging Premium you can carry on working – without loss of accuracy or time limits.

Reference track management



Tramline management

<sup>1</sup> SATCOR 15 / SATCOR 3 / SATCOR 3 FAST powered by Trimble RTX. SATCOR correction signals, RTK Bridging and RTK Bridging Premium are not available in all regions. Together with your CLAAS distributor, we will find the best solution for your individual requirements.


# A connected tractor is more productive.

## Digitalisation pays.

Digitalisation is a key factor in increasing your productivity and efficiency. Data generated in completely different places can be collected and evaluated centrally. This conserves your resources and improves your business processes.

To enable you to get more out of the XERION and your other machines, CLAAS offers a range of modules which allow systems, technology and working processes to be connected with each other, regardless of the manufacturer. Intelligent digitalisation matched to the requirements of your farm can reduce your workload significantly.

- Transfer and document machine and job data quickly
- Manage individual machines and the whole fleet efficiently
- Analyse working processes in detail and optimise them
- Analyse fields with ease and prepare simple application maps
- Create and manage field track intelligently
- Call up and manage farm data with intelligent farm management software
- Save valuable maintenance and service time with remote diagnostics



### NEW: CLAAS connect.

Everything we do revolves around your success, your machines and your farm. And everything you need is now on one platform – CLAAS connect.

With CLAAS connect, all your farm and machine data are clearly arranged in one place. Compare the performance of your machines on the spot to make the most of your fleet's potential. Manage individual service agreements, maintenance notifications, parts catalogues and operating manuals for all your machines. Order parts and consumables straight from your dealer through the integrated shops.

With track planning, you can easily create tracks for efficient fieldwork and manage them on the platform. Instantly create application maps based on satellite maps for precise, targeted application of seed and fertiliser. Send your jobs complete with tracks and application maps straight from CLAAS connect to the CEMIS 1200 terminal to ensure simple, precise execution on the field.

Discover how documentation runs in the background, recording your fieldwork reliably and automatically. Focus on your work and let CLAAS connect take care of the rest.

Need another machine in addition to your XERION? No problem! You can configure one at any time in CLAAS connect and ask your dealer to arrange a demonstration or prepare an offer.

## Three Connect packages to make your job easier.

The Connect packages get you on the right track to manage all your farm's digital tasks. Your CLAAS sales partner and digital specialist will set you up with all the functions you need for your business. Each package gives you a quick overview of your machine and service data in CLAAS connect. The higher level packages help you simplify data exchange between the machine and your office and plan and implement your year-round field work more efficiently.

## CLAAS connect packages for tractors.

## Connect Package 1

## Documentation

- CLAAS connect
- optional: farm licenses for CLAAS connect
- Machine connect

## Connect Package 2

Documentation

+ Steering system

- CLAAS connect
- optional: farm licenses for CLAAS connect
- Machine connect
- GPS PILOT CEMIS 1200

## Connect Package 3

Documentation

- + Steering system
- + Precision Farming
- CLAAS connect
- optional: farm licenses for CLAAS connect
- Machine connect
- GPS PILOT CEMIS 1200
- ISOBUS activations

Not all products are available worldwide. Please contact your dealer to check availability.

## Fast maintenance means more time in the field.





## One-piece bonnet.

The one-piece bonnet provides rapid access to all maintenance points. Four easily removable side panels provide additional access.

## Easy access.

The engine oil filter is positioned within the full frame for easy access. You can access the coolant reservoir when the bonnet is closed. The batteries are safely installed at the front.

## Double the maintenance interval.

We have raised the bar: the XERION needs to go to the workshop for engine servicing only once every 1,000 hours. Doubling the servicing interval results in significant cost savings.

## A XERION is undemanding.

The machine does whatever it can to minimise downtimes. The engine needs servicing just every 1,000 hours. And CEBIS tells you when.

## Simple radiator cleaning.

When maintenance does become due, it can be carried out quickly and effortlessly. The engine oil filter and cab air filter are very accessible. The radiator assembly can easily be opened and cleaned by the driver as required.

What's more, at the press of a button the driver can reverse the direction of the fan from the cab to blow dust and dirt away from the radiators in seconds.

## Clean engine intake air.

The XERION has an efficient system for precleaning the engine intake air. Cyclones separate out the coarse dirt which is then removed by the exhaust system. The PowerCore® engine air intake filter is extremely robust with high filtration performance.

## Maintenance maintains the value.

- 1,000 hour engine service interval
- One-piece bonnet for rapid access to all maintenance points
- Coolant reservoir can be accessed when the bonnet is closed
- PowerCore® filter for cleaning the engine intake air
- Batteries safely protected

# Whatever it takes. CLAAS Service & Parts.



## CLAAS service agreements.

Few factors are more crucial to the success of your business than the reliability of your machines. Which is why we offer transparent and predictably priced service products for your CLAAS machine which ensure a high degree of reliability.

## Machine connect.

Machine connect provides your service partner with all relevant data from machines equipped with telemetry. This makes remote diagnosis and remote support much easier. Servicing can be carried out more efficiently and machine availability is improved. All you have to do is give your consent.

The availability of products from CLAAS Service & Parts may vary according to country.



## Specially matched to your machine.

Precision-manufactured parts, high-quality consumables and useful accessories. Choose our comprehensive product range to be certain of receiving exactly the right solution to ensure 100% operating reliability for your machine.



## For your business: CLAAS FARM PARTS.

CLAAS FARM PARTS offers one of the most comprehensive ranges of multi-brand parts and accessories for all agricultural applications on your farm.



## Global supply.

The CLAAS Parts Logistics Center in Hamm, Germany, stocks almost 200,000 different parts and has a warehouse area of over 183,000 m<sup>2</sup>. This central spare parts warehouse delivers all ORIGINAL parts quickly and reliably all over the world.



## Your local CLAAS distributor.

Wherever you are, you can count on us to always provide you with the service and the contact people you need. Your CLAAS partners are on hand in your local area, ready to support you and your machine around the clock. With know-how, experience, commitment and the best technical equipment. Whatever it takes.

# The XERION: built to impress.



## Perfected.

- More performance: the entry-level XERION 4200 delivers
   462 hp and the XERION 5000 530 hp
- More comfort: the CEBIS touchscreen is built into the specially developed armrest
- More time in the field: the 1,000 hour maintenance interval cuts servicing costs by up to 38%
- More accuracy: CEMIS 1200 terminal for efficient precision farming

## Proven design concept.

- Four equal-sized wheels or dual tyres convert engine power into tractive power
- Full-frame construction can carry enormous loads of up
   15 t per axles at 50 km/h
- Two steered axles offer five steering modes for a wide range of applications
- CMATIC continuously variable transmission helps to save fuel

## Powerful drive.

- Powerful 6-cylinder engines are combined with a simple drive train
- Full torque from 1,000 rpm
- Idling speed reduced to 730 rpm in parked position
- Maximum 1,700 rpm required for heavy tillage work
- All engines have SCR technology, particulate filters and diesel oxidation catalyst in compliance with Stage V

## Unrivalled comfort.


- The spacious cab offers excellent all-round visibility and sound proofing
- The rotating cab in the TRAC VC is the most convenient reverse-drive system on the market
- The CMOTION multifunction control lever and CEBIS 12" touchscreen are designed for intuitive operation
- GPS PILOT CEMIS 1200 with ISOBUS implement control and task management

## Built to impress.



 $<sup>^{\</sup>scriptscriptstyle 1}$  Long wheelbase and balanced weight distribution for more tractive and lifting power

## SADDLE TRAC



<sup>&</sup>lt;sup>1</sup> Ideal weight distribution of 63:37 for working with heavy loads

5000 TRAC / TRAC VC					
EngineManufacturerMercedes-BenzMercedes-BenzMercedes-BenzNumber of cylinders666					
ManufacturerMercedes-BenzMercedes-BenzMercedes-BenzNumber of cylinders66					
Number of cylinders 6 6					
·					
Cubic capacity cm <sup>3</sup> 12800 12800 10700					
Nominal engine speed rpm 1900 1900 1900					
Lower engine idling speed (gear in neutral) rpm 730 730 730					
Upper engine idling speed rpm 1920 1920 1920					
Output at nominal engine speed (ECE R 120) <sup>1</sup> kW/hp 374/509 353/480 337/458					
Max. output (ECE R 120) <sup>1</sup> kW/hp 390/530 360/490 340/462					
Max. torque (ECE R 120) <sup>1</sup> Nm 2600 2400 2200					
Fuel tank I 740 740 740					
Auxiliary tank (190 I)   ● ○					
Urea tank 88 88					
Electrical system					
AC generator A/V 100 A / 24 V + 240 A / 12 V 100 A / 24 V + 240 A / 12 V 100 A / 24 V + 240 A / 12 V	/				
Batteries Ah/V 4 x 75 Ah, total 150/24, 150/12 4 x 75 Ah, total 150/24, 150/12 4 x 75 Ah, total 150/24, 150/12					
CMATIC transmission	<i>,,</i> 12				
Transmission type Hydrostatic-mechanical, split-power					
Output Four-wheel drive, permanent Four-wheel drive, permanent Four-wheel drive, permanent	[				
Max. speed km/h 50/40 50/40 50/40					
Longitudinal differential					
Eccom 5.5: rigid (without longitudinal differential)					
PTO speed rpm 1000 1000 1000					
Automatic PTO engagement / disengagement   • • • • • • • • • • • • • • • • • •					
Powered steering axles					
Differential locks 100% lockable, electrohydraulic actuation, lamella construction, with automatic function					
Brakes					
Service brake Hydraulically actuated wet multi-disc brakes, auxiliary-power-reinforced, acting on all wheels	Hydraulically actuated wet multi-disc brakes, auxiliary-power-reinforced, acting on all wheels				
Parking brake Electrohydraulically released spring-loaded brake					
Hydraulics					
Max. hydraulic tank capacity I 120 120 120					
Max. drawable volume I 80 80					
Main circuit (linkage, auxiliary spool valves)					
Max. operating pressure Mpa (bar) 20 (200) 20 (200) 20 (200)					
Max. flow rate					
Number of spool valves Max. 7 rear, max. 3 front Max. 7 rear, max. 3 front Max. 7 rear, max. 3 front					
Max. flow rate per spool valve					
Max. hydraulic output, total kW 58 58					
Power hydraulics (optional)					
Operating pressure Mpa (bar) 26 (260) 26 (260) 26 (260)					
Max. flow rate					
Max. hydraulic output, total kW 90 90 90					
Auxiliary hydraulics (optional)					
Operating pressure Mpa (bar) 20 (200) 20 (200) 20 (200)					
Max. flow rate					

5000 TRAC /

Drawbar load 3000

Drawbar load 2000

Drawbar load 3000

Drawbar load 4000

Drawbar load 15000

Drawbar load 4000

Raise, lower (press)

IV N, double-acting

Raise, lower (press)

vibration damping

7163

3600

15

16300

7884

3900

3791 to 3941

375 to 525

100 / 136 / 763

Position control, vibration

TRAC VC

max. kg Drawbar load 2500

Mpa (bar) III N, double-acting

8100

8400

905

damping

max. kg

max. kg

max. kg

max. kg

max. kg

kg

kg

mm

mm

mm

mm

mm

m

kg

mm

mm

Hitches

Piton Fix

Category

Front linkage

Max. lift range

Control function

Rear linkage Category

Selectable function

Selectable function

Overall length including linkages

(front retracted, rear horizontal)

Overall height depending on tyres

Overall length including linkages

Overall height depending on tyres

Ground clearance depending on equipment

(with tyres, full tank and standard equipment) Dimensions and weights for SADDLE TRAC

(front retracted, pivoting rear linkage horizontal)

Ground clearance depending on equipment

(with tyres, full tank and standard equipment) Data management and operator assistance systems

Control function

Wheelbase

Wheelbase

CEMOS

Smallest turning circle

Smallest turning circle

SADDLE TRAC kerb weight

TRAC kerb weight

up to 40 km/h

up to 50 km/h

Drawbar ball system

Continuous lift capacity Max. lift capacity

D40, D50 variable drawbar

Hitch ball for swanneck hitching

Continuous lift capacity / max. lift capacity / max. lift range kN / kN /

Dimensions and weights for TRAC and TRAC VC

Automatic hitch, D38 pin, spherical

Hitch with hitch ball, ball system 80

4500 TRAC /

Drawbar load 2500

Drawbar load 3000

Drawbar load 2000

Drawbar load 3000

Drawbar load 4000

Drawbar load 15000

Drawbar load 4000

III N, double-acting

Raise, lower (press)

IV N, double-acting

Raise, lower (press)

vibration damping

3791 to 3941

375 to 525

7163

3600

15

16300

7884

3900

Position control / draught control, Position control / draught control, Position control / draught control,

100 / 136 / 763

Position control, vibration

8100

8400

905

damping

TRAC VC

4200 TRAC /

Drawbar load 2500

Drawbar load 3000

Drawbar load 2000

Drawbar load 3000

Drawbar load 4000

Drawbar load 4000

III N, double-acting

Raise, lower (press)

IV N, double-acting

Raise, lower (press)

vibration damping

7163

3600

15

16000

7884

3900

3600

15

15600

375 to 525

3791 to 3941

375 to 525

100 / 136 / 763

Position control, vibration

8100

8400

905

damping

Drawbar load 15000

TRAC VC / SADDLE TRAC

CSM headland management ISOBUS and TIM GPS PILOT ready GPS PILOT CEMIS 1200 Machine connect - 5 year licence CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be All technical specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information

considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

purposes and ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.

## We want to make you the best in your field.

Everything we do is focused on you, our customers. We understand your daily challenges. Together with you, we develop agricultural technology that enables you to farm successfully and sustainably, now and in the future. Our digital solutions simplify complex processes and make your work so much more convenient.



CLAAS KGaA mbH Mühlenwinkel 1 33428 Harsewinkel Deutschland Tel. +49 5247 12-0 claas.com