



ARION	660	650	630	610	550	530	510
Dimensions and weights							
Height: centre of rear axle to cab roof (a)	mm	2166	2166	2166	2166	2166	2166
Overall height (b)	mm	3050	3050	3050	3050	3000	3000
Rear tyres		20.8 R 38	18.4 R 38				
Wheelbase (c)	mm	2820	2820	2820	2820	2564	2564
Length from front weight carrier to rear lower links (d)	mm	4818	4818	4764	4759	4508	4503
Weight	kg	7860-8335	6980-7830	6740-7600	6530-7470	6410-7260	6000-6940
Max. permissible total weight (40/50 km/h versions)	kg	12500	12500	11000	10250	11000	10250



Tractors

ARION

660 650 630 610
550 530 510



Intelligence gets more done.



ARION	660	650	630	610	550	530	510
Engine							
Manufacturer	DPS	DPS	DPS	DPS	DPS	DPS	DPS
Number of cylinders	6	6	6	6	4	4	4
Cubic capacity cm ³	6788	6788	6788	6788	4525	4525	4525
Variable geometry turbo	●	●	●	●	—	—	—
Compound turbo (two fixed geometry turbochargers, including one with wastegate)	—	—	—	—	●	●	●
Rated output (ECE R 120) ¹	kW/hp 129/175	129/175	114/155	99/135	114/155	99/135	85/115
Max. output (ECE R 120) ¹	kW/hp 136/185	136/185	121/165	107/145	121/165	107/145	92/125
Max. output with CPM (ECE R 120) ¹	kW/hp 151/205	—	—	—	—	—	—
Engine speed at maximum output rpm	2000	2000	2000	2000	2000	2000	2000
Rated output type approval value for CMATIC models ²	kW 144	128	115	102	117	106	91
Max. output type approval value for CMATIC models ²	kW 154	145	130	116	124	118	104
Rated output type approval value for HEXASHIFT models ²	kW —	141	115	102	117	106	91
Max. output type approval value for HEXASHIFT models ²	kW —	151	130	116	124	118	104
Max. torque (ECE R 120) ¹	Nm 849	754	703	640	697	619	562
(with CPM)	—	—	—	—	—	—	—
Engine speed at max. torque rpm	1500	1500	1500	1500	1500	1500	1500
Max. fuel tank capacity l	367	367	367	367	242	242	242
Oil-change interval h	500	500	500	500	500	500	500
CMATIC continuously variable transmission							
Transmission	EQ 220	EQ 200					
Speeds (min.-max.) km/h	0.05-50/40	0.05-50/40	0.05-50/40	0.05-50/40	0.05-50/40	0.05-50/40	0.05-50/40
REVERSESHIFT clutchless reverser	●	●	●	●	●	●	●
HEXASHIFT powershift transmission							
Ratios F/R	—	24/24	24/24	24/24	24/24	24/24	24/24
Min. speed at 2200 rpm km/h	—	1.58	1.58	1.73	1.58	1.73	1.68
Max. speed km/h	—	40/50	40/50	40/50	40/50	40/50	40/50
REVERSESHIFT clutchless reverser	—	●	●	●	●	●	●
Powershift speeds	—	6	6	6	6	6	6
Electrohydraulically controlled ranges	—	4	4	4	4	4	4
Min. speed with creep gear at 2200 rpm km/h	—	0.40	0.40	0.43	0.40	0.43	0.42
Rear axle							
Flanged axle	●	●	●	●	●	●	●
Quick-release axle	○	○	○	—	○	—	—
Electrohydraulically activated differential locks	●	●	●	●	●	●	●
Automatic differential lock	●	●	●	●	●	●	●
Park lock	○	○	○	○	○	○	○
Max. rear tyres	m 710/60 R 42	710/60 R 42	650/65 R 42	650/65 R 38	650/65 R 38	650/65 R 38	650/60 R 38
Max. diameter of rear tyres m	1.95	1.95	1.95/1.85	1.85	1.85	1.85	1.75
Oil-change interval h	1500	1500	1500	1500	1500	1500	1500
PTO							
Wet multi-disc clutch	●	●	●	●	●	●	●
Remote control of engagement and emergency stop	●	●	●	●	●	●	●
540/1000	●	●	●	●	●	●	●
540/540 ECO / 1000/1000 ECO	○	○	○	○	○	○	○
Changeable PTO stub	●	●	●	●	●	●	●
1¾" PTO stub; 6, 8 and 21 splines	□	□	□	□	□	□	□
Automatic PTO engagement / disengagement	●	●	●	●	●	●	●
Four-wheel drive front axle							
Rigid front axle	—	—	●	●	●	●	●
Rigid and braked front axle	●	●	—	—	—	—	—
PROACTIV front axle suspension	—	—	□	□	□	□	□
PROACTIV front axle suspension with braked front axle	□	□	□	□	□	□	□
Automatic 4-wheel drive	●	●	●	●	●	●	●
Optimum turning radius m	5.5	5.5	5.5	5.5	5.35	4.95	4.95

ARION	660	650	630	610	550	530	510
Hydraulics							
Load-sensing circuit 110 l/min	●	●	●	●	●	●	●
Load-sensing circuit 150 l/min	○	○	○	○	○	○	○
Max. operating pressure bar	200	200	200	200	200	200	200
Number of mechanical spool valves (CIS)	2-4	2-4	2-4	2-4	2-4	2-4	2-4
Number of electronic spool valves (CEBIS / CIS+)	3-4	3-4	3-4	3-4	3-4	3-4	3-4
Two central electronic spool valves, operated from ELECTROPILOT	□	□	□	□	□	□	□
Flow rate control	●	●	●	●	●	●	●
Rear linkage							
Max. lifting capacity at ball ends kg	8000	8000	8000	7500	8000	7500	7500
Continuous lift capacity at 610 mm kg	5100	5100	5100	5100	5100	5100	5100
Vibration damping	●	●	●	●	●	●	●
External controls	●	●	●	●	●	●	●
Active wheel slip control	○	○	○	○	○	○	○
ISOBUS socket	○	○	○	○	○	○	○
25 amp socket	●	●	●	●	●	●	●
Front linkage							
Lift capacity t	4	4	4	4	4	4	4
Front PTO 1000 rpm	○	○	○	○	○	○	○
Vibration damping	●	●	●	●	●	●	●
Position control for CEBIS version	○	○	○	○	○	○	○
External operation	○	○	○	○	○	○	○
Additional hydraulic connections	○	○	○	○	○	○	○
External operation of additional connections	○	○	○	○	○	○	○
ISOBUS socket	○	○	○	○	○	○	○
Trailer socket	●	●	●	●	●	●	●
25 amp socket	○	○	○	○	○	○	○
Cab							
CIS	—	●	●	●	●	●	●
CIS+	●	○	○	○	○	○	○
CEBIS	○	○	○	○	○	○	○
4-pillar cab	●	●	●	●	●	●	●
5-pillar cab	○	○	○	○	○	○	○
4-point suspension	●	●	●	●	●	●	●
Air conditioning	●	●	●	●	●	●	●
Automatic climate control	○	○	○	○	○	○	○
Passenger seat with integral cool box	●	●	●	●	●	●	●

¹ Meets ISO TR 14396

² Performance data fit criteria for admissibility

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual. All technical specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information purposes and ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.